

ICS 47.020
U 01

CB

CB/T 2999—2020
CB/T 2999—2010

**Basic requirements and evaluation methods of design conditions
for ship design organizations**

2020 - 04 - 24

2020 - 10 - 01

		III
1		1
2		1
3		1
3.1		1
3.2		1
3.3		1
3.4		2
3.5		2
3.6		2
3.7		2
4		2
4.1		
4.2		
5		3
6		5
6.1		
6.2		
6.3		
6.4		
7		6
7.1		
7.2		
7.3		

9.2	60	
9.3	60	
9.4		60
9.5	30	
9.6	30	
9.7	60	
10		 13
10.1		
10.2		100
10.3	50	
10.4	50	

GB/T 1.1—2009

CB/T 2999—2010

, CB/T 2999—2010

 $\dot{I}$

a

4.1 4.2.1 2010 4.1 4.2.1

b

2 2010 2

C

“ ”

2010

7.4 7.5.3 7.5.4

d

“ ” “ ”

7.5 7.6

e

“ ”

9.2 2010 7.6

f

22

8 2010

1



2

~

GB/T 19001

BC

IBC

IGC

GC

CSR

HCSR

3



3.1

ship design

1(

		a ð
		b ð
		c
		a ð ð
		b 20 m
		ð SPAR ð

2

		1	$L \geq 220\text{ m}$	$L \geq 150\text{ m}$	$L \geq 60\text{ m}$
		2	HCSR $L \geq 150\text{ m}$	HCSR, $L \geq 100\text{ m}$	HCSR, $L \geq 60\text{ m}$
		3	5000TEU	3000TEU	500TEU
		4	HCSR $L \geq 150\text{ m}$	HCSR $L \geq 100\text{ m}$	HCSR $L \geq 60\text{ m}$
		1	/	$L \geq 100\text{ m}$	$L \geq 100\text{ m}$
		2			

6.4.2 试验

6.4.2.1 将试样按图 7 所示尺寸加工成 10

6.4.2.2 将试样按图 8 所示尺寸加工成 800
70 %
A

7

7.1

5 续 续

	25	16	8
		10	5

7.5.2 F•r9đp%19%+ÜXÇ 1V0#ŠD %÷1V 2%AE`CÂŸñ r9.pf" r9đH A,s a +Üf <)• )FY†Tcæ P—#Ÿ € %BYW•q&`Cí 6

7 4 4

		a		30			5		
			10						
		b	GB/T 19001	0	0	30	0		
			30						
		c				20		3	
		d							

8 试验

		a 60 60 2 b 30 6 24 60 2 1 1 0.5 c 40 5 d 40 2
		a 30 60 2 b 15 3 60 3 12 2 1 0.5 c 40 5 d 40 2
		a 15 60 2 b 60 2 8 0.5 1 c 40 5 d 40 2
		a 30 60 2 b 15 3 60 3 12 2 1 0.5 c 40 5 d 40 2
		a 20 60 2 b 60 2 10 0.5 1 c 40 5 d 40 2 a 10 60 2 b 60 2 5 0.5 1 c 40

9

9.1

30 60 60 60
30 60 300
210

9.2 60

⌘ ⌘ ⌘

b

10

c

10

3

2

9.4

60

1

1

10

a

b

5

1

c

d

10

10

5

10

9.5

30

1

1

10

a

b

10

c

d

5

10

9.6

30

5

1

1

10

a

b

c

d

5

10

7

10

a

~

30

9.7

60

9.7.1

1

1

10

10

5

9.7.2

